


N-沟道功率 MOS 管
JFUX5N50D(TO-251)/JFDX5N50D(TO-252)

- **特点:** 导通电阻低 开关速度快 输入阻抗高 符合RoHS规范
- **FEATURES:** ■ LOW ON-RESISTANCE ■ FAST SWITCHING ■ HIGH INPUT RESISTANCE ■ RoHS COMPLIANT
- **应用:** 电子镇流器 电子变压器 开关电源
- **APPLICATION:** ■ ELECTRONIC BALLAST ■ ELECTRONIC TRANSFORMER ■ SWITCH MODE POWER SUPPLY

● 最大额定值 (Tc=25°C)
● Absolute Maximum Ratings (Tc=25°C) TO-251//252

参数 PARAMETER	符号 SYMBOL	额定值 VALUE	单位 UNIT
漏-源电压 Drain-source Voltage	V _{DS}	500	V
栅-源电压 gate-source Voltage	V _{GS}	±30	V
漏极电流 Continuous Drain Current TC=25°C	I _D	5.0*	A
漏极电流 Continuous Drain Current TC=100°C	I _D	3.0*	A
最大脉冲电流 Drain Current — Pulsed ①	I _{DM}	20*	A
耗散功率 Power Dissipation	P _{tot}	50	W
最高结温 Junction Temperature	T _J	150	°C
存储温度 Storage Temperature	T _{STG}	-55-150	°C
单脉冲雪崩能量 Single Pulse Avalanche Energy ②	E _{AS}	280	mJ



*漏极电流由最高结温限制

*Drain current limited by maximum junction temperature

● 电特性 (Tc=25°C)
● Electronic Characteristics (Tc=25°C)

参数 PARAMETER	符号 SYMBOL	测试条件 TEST CONDITION	最小值 MIN	典型值 TYP	最大值 MAX	单位 UNIT
漏-源击穿电压 Drain-source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	500			V
击穿电压温度系数 Breakdown Voltage Temperature Coefficient	ΔBV _{DSS} / ΔT _J	I _D =250uA, Referenced to 25°C		0.6		V/°C
栅极开启电压 Gate Threshold Voltage	V _{GS(TH)}	V _{GS} =V _{DS} , I _D =250μA	2.0		4.0	V
漏-源漏电流 Drain-source Leakage Current	I _{DSS}	V _{DS} =500V, V _{GS} =0V, T _J =25°C			25	μA
		V _{DS} =400V, V _{GS} =0V, T _J =125°C			250	μA
跨导 Forward Transconductance	g _{fs}	V _{DS} =15V, I _D =2.5A ③	2.4			S

N-沟道功率 MOS 管
JFUX5N50D(TO-251)/JFDX5N50D(TO-252)

参数 PARAMETER	符号 SYMBOL	测试条件 TEST CONDITION	最小值 MIN	典型值 TYP	最大值 MAX	单位 UNIT
栅极漏电流 Gate-body Leakage Current ($V_{DS} = 0$)	I_{GSS}	$V_{GS} = \pm 30V$			± 100	nA
漏-源导通电阻 Static Drain-source On Resistance	$R_{DS(ON)}$	$V_{GS} = 10V, I_D = 2.5A$ ③		1.35	1.5	Ω
输入电容 Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 25V$ $F = 1.0MHz$		580		pF
输出电容 Output Capacitance	C_{oss}			45		
反馈电容 Feedback Capacitance	C_{rss}			17		
关断延迟 Turn -Off Delay Time	$T_d(off)$	$V_{DD} = 300V, I_D = 4.0A$ $R_G = 25\Omega$ ③		20		ns
栅极电荷 Total Gate Charge	Q_g	$I_D = 5.0A, V_{DS} = 480V$ $V_{GS} = 10V$ ③		26		nC
栅源电荷 Gate-to-Source Charge	Q_{gs}			4		nC
栅漏电荷 Gate-to-Drain Charge	Q_{gd}			15		nC
二极管正向电流 Continuous Diode Forward Current	I_S				5.0	A
二极管正向压降 Diode Forward Voltage	V_{SD}	$T_j = 25^\circ C, I_S = 5.0A$ $V_{GS} = 0V$ ③			1.6	V
反向恢复时间 Reverse Recovery Time	t_{rr}	$T_j = 25^\circ C, I_f = 5.0A$ $di/dt = 100A/\mu s$ ③		220		ns
反向恢复电荷 Reverse Recovery Charge	Q_{rr}			1.0		μC

●热特性
●Thermal Characteristics

参数 PARAMETER	符号 SYMBOL	最大值 MAX	单位 UNIT
热阻结-壳 Thermal Resistance Junction-case	R_{thJC}	2.50	$^\circ C/W$
热阻结-环境 Thermal Resistance Junction-ambient	R_{thJA}	110.0	$^\circ C/W$

注释(Notes):

- ① 脉冲宽度：以最高结温为限制
 Repetitive rating: Pulse width limited by maximum junction temperature
- ② 初始结温= $25^\circ C$, $V_{DD} = 50V$, $L = 24mH$, $R_G = 25\Omega$, $I_{AS} = 5.0A$
 Starting $T_j = 25^\circ C$, $V_{DD} = 50V$, $L = 24mH$, $R_G = 25\Omega$, $I_{AS} = 5.0A$
- ③ 脉冲测试：脉冲宽度 $\leq 300\mu s$ ，占空比 $\leq 2\%$
 Pulse Test : Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$

N-沟道功率 MOS 管

JFUX5N50D(TO-251)/JFDX5N50D(TO-252)

● 特性曲线




图 1 输出特性曲线, Tc=25°C

Fig1 Typical Output Characteristics, Tc=25°C




图 2 输出特性曲线, Tc=150°C

Fig2 Typical Output Characteristics, Tc=150°C




图 3 归一化导通电阻与温度曲线
Fig3 Normalized Resistance Vs. Temperature




图 4 二极管正向电压曲线
Fig4 Typical Source-Drain Diode Forward Voltage




图 5 最大漏极电流与壳温曲线
Fig5 Maximum Drain Current Vs. Case Temperature




图 6 最大安全工作区曲线
Fig6 Maximum Safe Operating Area